

LOCTITE®

Prevent fretting and corrosion while securing bearings with Loctite® 641 Retaining Compound.

Make any size gasket with Loctite® 518 Flange Sealant.

Protect pump against chemical attack and erosion with Loctite® Nordbak® 7221 Chemical Resistant Coating.

Prevent rust and seizure of power end bolts with Loctite® 8023 Marine Grade Anti-Seize.

Prevent key wear with Loctite® 243 Threadlocker or repair key wear with Loctite® 660 Retaining Compound.

Rebuild and protect worn volutes with Loctite® Nordbak® 7218 Wearing Compound and/or Loctite® Nordbak® 7227 or 7228 Brushable Ceramics.

Prevent set screws from working loose with Loctite® 222 or Loctite® 243 Threadlockers.

Restore, coat, and protect impeller vanes with Loctite® Nordbak® 7227 or 7228 Brushable Ceramics.

Secure and prevent leakage between oil seals and housing with Loctite® 243 or Loctite® 248 Threadlockers.

Prevent corrosion and seizure of gland assembly nuts and seizure of the impeller to the shaft with Loctite® 8023 Marine Grade Anti-Seize.

Lubricate and prevent damage to o-rings with Loctite® 8104.

Rebuild worn shafts with Loctite® 3478 Superior Metal.

Seal threaded fittings with Loctite® 577 or Loctite® 572 Thread Sealants.

Keep mounting bolts tight with Loctite® 2701 Threadlocker.

Prevent corrosion and secure casing bolts and adapter bolts with Loctite® 243 Threadlocker.

Seal and protect flushing connectors with Loctite® 572 Thread Sealant.

Increase Pump Reliability and Performance with Loctite® Technology

